ARTIMO

Hardware Specs

Designed to meet the demands of modern broadcast and production environments, Artimo redefines flexibility, creativity, and practicality in any studio setting.



Specification	Details
Payload Capacity	ENG or Box style broadcast camera, ENG or Mini-Box lenses, 19” Teleprompter
Max. Payload	40 kg (88lbs)
Optical Height Floor to Tilt Axis	Min.: 0.7m Max
Pan Range	±179 deg (total 358 deg)
Tilt Range	With prompter: ±25 deg (50 deg total) Without prompter, throughout lift range: ±36.5 deg (73 deg total) Without prompter, limited lift range[1]: ±85 deg (170 deg total)
Pan Speed	Min. : 0.01 deg/sec Max. : 90 deg/sec
Tilt Speed	Min. : 0.01 deg/sec Max. : 60 deg/sec
Floor Speed	Min. : 0.01 cm/sec Max. : 50 cm/sec
Lift Speed	Min. : 0.01 cm/sec Max. : 15 cm/sec
Floor (xy) Absolute Accuracy	±1.25cm
Max. System Height	2.5m
System Weight	<185 kg
System Footprint - Max. Width	86cm
Virtual Tracking Data	Included

1 Limited lift range includes all but the last 10% at the upper and lower extremes of the lift’s total travel.