



⚠ CAUTION: Before you set up and operate this product, see the “Important Safety Instructions” in your Manual.



- 1** Attach the handles to the front rack-mount tabs by aligning the handle with the round holes and fastening from the rear with the supplied screws.
- 2** Use the supplied Rack Mount Kit to mount the XPression system in a 19" EIA equipment rack. If the version of the XPression system purchased does not use a rack-mount, refer to the instructions for installing the mounting feet.
- 3** Plug the supplied Keyboard into the upper **USB** port.
- 4** Plug the supplied Mouse into the lower **USB** port.



- 5** Connect a Monitor (customer supplied) to the **DVI 1** port.
- 6** (Optional) Connect a second monitor to the **DVI 2** port to provide space for virtual preview channels, custom applications, web page capture, and more.
KVM extenders (customer supplied) are required when the XPression System monitor, keyboard, and mouse are located remotely from the rack room.
- 7** Plug an Ethernet cable from your Local Area Network into one of the **Ethernet** ports.
XPression Systems can run standalone or accept a connection to a production network. The network connection is also used for the Smart GPI Feature.

Continued on other side...

?

Need Help?

Technical Support: (+1) 613-652-4886
Email: techsupport@rossvideo.com



- 8** Connect the Matrox x.Mio Audio Breakout cable to the **Matrox** port.
- 9** Connect the Matrox x.Mio Video Breakout cable to the **Matrox** port.
- 10** Connect up to 4 channels of video output (or 2 channels video + key) to the HD/SDI **Video Out** BNC connectors.
XPression Systems support SDI / HD-SDI inputs. If you require analog inputs, additional outboard analog to digital conversion equipment is available from Ross Video.
- 11** Connect up to 2 channels of video input (or 1 channel video + key) to the HD/SDI **Video In** BNC connectors.
XPression Systems support SDI / HD-SDI inputs. If you require analog inputs, additional outboard analog to digital conversion equipment is available from Ross Video.
- 12** Connect audio out and audio in cables from the **AES/EBU OUT** and **IN** connectors on the breakout cable to their required destination.
- 13** Connect your house reference GenLock signal to the **ANALOG REF IN** BNC connector on the breakout cable.
XPression Systems accept analog black bursts or tri-level sync as reference inputs. Tri-level sync is recommended for HD installations.
- 14** Connect power cords from the **AC** Ports on the XPression system to the mains power.
XPression system power supplies are auto-sensing and can use either 110 VAC or 220 VAC.
- 15** Press the Power button on the front of the XPression System.
Ross Video recommends shutting down XPression Systems from the Windows operating system.
- 16** Click the XPression user account icon to log onto the system.
- 17** Launch XPression from the **Start** menu.