

FUJIFILM
Value from Innovation

HA18x5.5



FUJINON


HA18x5.5BE RM/RD*/ZD**




Zoom Ratio / Format	18X / 2/3"
Focal Length	5.5 to 100 mm
Extender	(2X) 11 to 200 mm
Maximum Relative Aperture	1:1.8 (5.5 ~ 62 mm) 1:2.9 (100)
Maximum Photometric Aperture T-No.	1:1.9 (5.5 ~ 62 mm) 1:3.1 (100)
Angular Field of View 16:9 Aspect Ratio	5.5 mm 82° 10' x 52° 13' 100 mm 5° 29' x 3° 05' (2X) 11 mm 47° 06' x 27° 32' 200 mm 2° 45' x 1° 33'
M.O.D. from Image Plane	0.69 m
M.O.D. from Front of Lens	0.4 m
Object Dimensions at M.O.D.	5.5 mm 800 x 450 mm 100 mm 44 x 25 mm (2X) 11 mm 395 x 222 mm 200 mm 22 x 12 mm
Filter Size	M127 x 0.75mm (In Hood Mounting Only)
Dia φ x Length (w/o Hood)	φ95 x 240.5
Weight (w/o Hood)	1.97 kg / 2.04 kg* / 2.10 kg**
Options	16 Bit Encoders (ZD Only) / Quick Frame
Features	Inner Focus / Zoom Limit / Quick Zoom / Virtual Serial Com / PC / Macro / 16 Bit Encoders (RM/RD)

ACCESSORIES: REAR CONTROLS DIGI POWER REAR CONTROL KITS


MS-11D Manual Focus/Servo Zoom
For use with RM/ZM type lenses.




SS-11D Servo Focus/Servo Zoom
For use with RM/ZM type lenses.




SS-13D Servo Focus/Servo Zoom
For use with RM/ZM type lenses.




MS-11 Manual Focus/Servo Zoom



SS-11 Servo Focus/Servo Zoom
Not available on HA42x, HA36x and A36.



MM-11 Manual Focus/Manual Zoom
Not available on HA42x, HA36x and A36.



- A. CFC-990 Flex Cable
- B. FMM-6B/FMM-8* Focus Manual Module
- C. ZMM-6 Zoom Manual Module
- D. SRD-92B Zoom Demand
- E. FSM-30B Focus Servo Module
- F. MCA-7 Mounting Clamp
- G. FSD-11 Focus Demand
- H. CZH-14 Zoom Handle
- I. CFH-3 Focus Handle

*FMM-8 for use with S16x7.3

*Specify camera type.

**FMM-3C for use on HA42x and HA25x

For Sales Contact Information go to
www.Fujinon.com