

[\(../index.html\)](#)

Is Your Future (../index.html)

[Portfolio ▾](#)[Support ▾](#)[News ▾](#)[Contact \(../Contact/contact.html\)](#)[Home \(../index.html\)](#) [Services - Broadcast Products](#)

Encoding

[Serial Box \(product.html\)](#)
[Custom Encoding \(custom.html\)](#)
[Focus & Zoom \(fz.html\)](#)
[Wireless option \(wireless.html\)](#)

Jib & Crane

Camera Head

Serial Box

[\(pix/sbox.jpg\)](#)[\(pix/sbox_B.jpg\)](#)

Encodacam Serial Box V.4b

Our Serial box provides an easy "plug and play" way to set up your virtual production system. We use rugged and reliable Lemo connectors that connect to the moving encoder axes. It is a stable and "Broadcast Proven" reliable tracking system in industry.

L*W*H	6.5"*6.3"*2.03" (160mm*160mm*51.5mm)
Weight	2 pounds (907g)
Encoders	Standard: 6 channels with Index Optional: 8 channels with Index
Lens	1 serial port with focus and zoom data Canon and Fujinon (Broadcast) ENG lens ready
Sync	Internal sync, Tri Level Sync or Black Burst sync
Protocol	Kuper or Thoma
Rendering	Brainstorm, VisRt, Orad, Ross Expression, Lightcraft Prevision, SolidTrack MotionBuilder
Streaming	RS232 and RS422 , DB9 connector Kuper: bi-directional communication Thoma: simplex communication
Power	AC: 110~240V Optional: DC: 9~35 V

General Lift International Inc.

Phone: + (310) 414 0717 Email: info@general-lift.com (<mailto:info@general-lift.com>)

Address: 111 Maryland Street, El Segundo, CA 90245, U.S.A.

