

Production Technology Experts



Prompter Selection Guide 877-TEKSKIL Tekskil.com		520-PT Load: 70 lbs.		600-PT Load: 120 lbs.		700-PT Load: 200 lbs.		
								
Specifications		15ER Prompter	17ER Prompter	17E Prompter	17P Prompter	19SE Prompter	19SP Prompter	22P Prompter
Brightness (cd/m²)		700	700	700	1000	700	1000	1200
Contrast Ratio		2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1
Power Consumption (12 VDC)		28 Watts	40 Watts	40 Watts	45 Watts	40 Watts	45 Watts	50 Watts
Panel Weight		7 lbs.	9 lbs.	12 lbs.	12 lbs.	14 lbs.	14 lbs.	16 lbs.
Warranty		3 Years	3 Years	3 Years	5 Years	3 Years	5 Years	5 Years
Prompter Options	Beamsplitters							
	Standard 16:9 HD lens	✓	✓	✓	✓	✓	✓	--
	Wide Angle 16:9 HD lens	--	--	✓	✓	✓	✓	✓
	Tally Option							
	Front mount single-stage 3x3 LED cluster	✓	✓	✓	✓	✓	✓	✓
	Top mount dual-stage LED bars & Cam #	✓	✓	✓	✓	✓	✓	✓
	Timing Option							
	6 digit VITC SMPTE clock 2.3" high LEDs	✓	✓	✓	✓	✓	✓	✓
	Aux/Talent Assist Monitors							
	19" LED Edge-lit 16:9	--	--	✓	✓	✓	✓	✓
22" LED Edge-lit 16:9	--	--	--	--	✓	✓	✓	

Tekskil Displays feature: Sophisticated power management to prevent image distortion, electrical noise and display damage
 Signal conditioning to eliminate ground loops and drop-outs
 Temperature control elements, including twin cooling fans to prevent image loss, back light failure and circuitry overheats

Tekskil Prompting Systems feature: Integrated stabilization and dampening elements to minimize prompter vibration and lurching during camera movement
 Micro-truss construction provides optimal strength, balance and weight for **greatly** reduced pan/tilt servo stress and failure.