



XPression Engines Software and Hardware Compatibility Matrix

XPression	HD-SDI			IP SMPTE ST 2022-7 & 2110				12G SDI								
	1RU	2RU	4RU	1RU	2RU	4RU	1RU	2RU	4RU							
Hardware Edition ▶	XPN-1RU-M9	XPN-1RU-L-M9	XPN-1RU-RS2-M9 ^{†††}	XPN-2RU-M9	XPN-4RU-M9	XPN-1RU-IP-D2BL-M9 ^{**}	XPN-2RU-IP-D2BL-M9 ^{**}	XPN-4RU-IP-D2BL-M9 ^{**}	XPN-1RU-IP-Q2BL-M9 ^{**}	XPN-1RU-RS2-M9 ^{†††}	XPN-1RU-12G-M9 ^{††}	XPN-2RU-12G-M9 ^{††}	XPN-2RU-RS2-M9 ^{†††}	XPN-4RU-12G-M9 ^{††}	XPN-4RU-12G-LL-M9 ^{†††}	XPN-4RU-RS2-M9 ^{†††}
Software Edition ▼																
PRIME XPR1	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
STUDIO SCE XSTS	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
STUDIO STANDARD XST3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
STUDIO FLEX XSTF	●	■	●	●	●	●	●	●	●	●	■	●	■	●	●	●
BlueBox SCE XBBS	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
BlueBox XBB3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
BlueBox FLEX XBBF	●	■	●	●	●	●	●	●	●	●	■	●	■	●	●	●
CLIPS 1-CHANNEL XCLS	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
CLIPS 2-CHANNEL XCLD	●	■	●	●	●	●	●	●	●	●	●	●	●	●	●	●
CLIPS 4-CHANNEL XCLF	●	■	●	●	●	●	●	●	●	●	■	●	■	●	●	●

^{**}2x 25G SFP28 Cages and, does not support SMPTE ST 2022-6
^{††} Only has 4 HD-BNCs and cannot support more than 4 signals (Supports single-channel UHD only)
^{†††} Capabilities differ when using HD-SDI or UHD-SDI inputs and/or outputs

Ross Video has a complete range of technical services available to ensure that your XPression installation is a success.

Operational Training can be provided at Ross Video, on-site or on the web. Experienced Ross operators will teach your staff to get the most out of your new system and enhance your production.

Commissioning is a service to help get your graphics system properly configured, connected, and installed. This service is performed by factory trained Ross technical staff.

Technical Training can be provided at Ross Video, on-site or on the web. Technical training will teach your engineering staff the technical details of the system you have purchased. System configuration, interfaces, databases, and routine maintenance procedures are some of the topics covered.

XPression comes standard with a 1-year system warranty (parts / labor & software updates) and 5-Years for Hard Disk Drives. **Extended Warranties** on hardware and software maintenance are available for an annual fee. Technical advice is available on-line, by telephone, or email to Ross Video – **Included for the life of your system.**



XPN-1RU-RS2-M9

Dimensions

Height	Width	Depth
4.3 cm (1.69")	43.8 cm (17.25")	65.6 cm (25.8")

Weight

Net Weight	Gross Weight When Shipped
12.42 kg (21.6 lbs.)	12.5 kg (27.6 lbs.)

Hardware

Chassis	1RU Chassis (rackmount)
Power Supply	2x 675W power supplies (redundant) Voltage Range 100-240 VAC Input Current 3.7 A- 7.4 A
Power Consumption	@115VAC, Idle 83.416W - Max 454.3W
Fan Noise	Between 36dB to 46dB
System Drive	512G (2x Z Turbo 512GB PCIe-4x4 2280 TLC M.2 Solid State Drive in RAID1)
Media Drive	3.8TB (2x HP Z Turbo 4TB PCIe-4x4 2280 M.2 3rd Solid State Drive in RAID1)
CPU	Intel® Xeon® W5-2455, 12-Core, 30 MB Intel® Smart Cache, 3.2 GHz, Max Turbo Frequency 4.6 GHz
Memory	64GB (4x16GB) 4800MT/s DDR5 RDIMM with ECC
GPU	NVIDIA™ RTX 4000 Ada 20GB GDDR6, 4x Display Port 1.4a Ports
Video I/O	HD-SDI, 12G SDI NDI®
O/S	Microsoft® Windows® 11 Professional for Workstation

Inputs / Outputs

Video	4x HD-BNC out only and 4 Bi-directional HD-BNC for up to 4 Channels (Video/Key Pair) of up to 12G*
Audio	Embedded Audio Only
Reference	1x Analog Black Burst (Bi-Level Sync) or Tri-Level Sync input

NDI® is a registered trademark of VizRT NDI AB

*Number of channels of 12G output available may be affected by software licenses and/or system hardware

Control

Ethernet	1x RJ-45 1G Ethernet Port 1x RJ-45 10G Ethernet Port
Serial	1x RS-232 Port 2x P/S2 Ports
GPI	Unlimited RossTalk™ Smart GPI over TCP/IP
USB	Front Panel - 2x USB 3.1 (Type A) - 2x USB Type C Rear Panel - 2x USB 3.1 (Type A)

Included Accessories

Rackmount Kit	Slide rails, handles, and mounting hardware
Keyboard	Standard USB Windows PC Keyboard (US English)
Mouse	USB 2-button mouse
Security Key Software	Either USB Hardware License or Software-based Product Key provided with software purchased separately

Video I/O Formats

480i 29.97fps (NTSC) | 576i 25fps (PAL) |
720p 50fps | 720p 59.94fps | 720p 60fps |
1080i 25fps | 1080i 29.97fps | 1080p 23.976fps |
1080p 24fps | 1080p 25fps | 1080p 29.97fps |
1080p 30fps | 1080p 50fps | 1080p | 59.94fps |
1080p 60fps | 2160p 23.976fps | 2160p 24fps |
2160p 25fps | 2160p 29.97fps | 2160p 30fps |
2160p 50fps | 2160p 59.94fps | 2160p 60fps

Supported Image File Formats

*.tga | *.tif | *.psd | *.bmp | *.jpg | *.gif | *.png

Supported Clip File Formats

AVI | MPEG† | QuickTime† | Sequential Images

† Available in the 32-bit editions only

Warranty

12-Month System Warranty (parts / labor)

Specifications subject to change without notice