XPression Engines Software and Hardware Compatibility Matrix

XPression / Hardware Edition ▶ / Software Edition ▼	HD-SDI 1RU XPN-1RU-LL-M9	HD-SDI 1RU XPN-1RU-M9	HD-SDI 2RU XPN-2RU-M9	HD-SDI 4RU XPN-4RU-M9	IP 1RU XPN-1RU-IP-D25L-M9**	IP 2RU XPN-2RU-IP-D10-M9*	IP 2RU XPN-2RU-IP-D25L-M9	IP 4RU XPN-4RU-IP-D25L-M9**	IP 4RU XPN-4RU-IP-Q25L-M9**	12G SDI 1RU XPN-1RU-12G-M9††	12G SDI 2RU XPN-2RU-12G-M9††	12G SDI 4RU XPN-4RU-12G-M9††	12G SDI 4RU XPN-4RU-12G-LL-M9†††
PRIME XPR1-0001	●	●	●	●	●	●	●	●	●	●	●	●	●
STUDIO SCE XSTS-0001	●	●	●	●	●	●	●	●	●	●	●	●	●
STUDIO STANDARD XST3-0001	●	●	●	●	●	●	●	●	●	●	●	●	●
STUDIO FLEX XSTF-0001	■	●	●	●	●	■	●	●	●	■	■	■	●
BlueBox SCE XBBS-0001	●	●	●	●	●	●	●	●	●	●	●	●	●
BlueBox XBB3-0001	●	●	●	●	●	●	●	●	●	●	●	●	●
BlueBox FLEX XBBF-0001	■	●	●	●	●	■	●	●	●	■	■	■	●
CLIPS 1-CHANNEL XCLS-0001	●	●	●	●	●	●	●	●	●	●	●	●	●
CLIPS 2-CHANNEL XCLD-0001	■	●	●	●	●	●	●	●	●	●	●	●	●
CLIPS 4-CHANNEL XCLF-0001	■	●	●	●	●	■	●	●	●	■	■	■	●

*2x 10G SFP28 Cages Does Not Support UHD
**2x 25G SFP28 Cages and, does not support SMPTE ST 2022-6
†† Only has 4 HD-BNCs and cannot support more than 4 signals (Supports single-channel UHD only)
†††Capabilities differ when using HD-SDI or UHD SDI inputs and/or outputs

Ross Video has a complete range of technical services available to ensure that your XPression installation is a success.

Operational Training can be provided at Ross Video, on-site or on the web. Experienced Ross operators will teach your staff to get the most out of your new system and enhance your production.

Commissioning is a service to help get your graphics system properly configured, connected, and installed. This service is performed by factory trained Ross technical staff.

Technical Training can be provided at Ross Video, on-site or over the web. Technical training will teach your engineering staff the technical details of the system you have purchased. System configuration, interfaces, databases, and routine maintenance procedures are some of the topics covered.

XPression comes standard with a 1-year system warranty (parts / labor & software updates) and 5-Years for Hard Disk Drives. **Extended Warranties** on hardware and software maintenance are available for an annual fee. Technical advice is available on-line, by telephone, or email to Ross Video – **Included for the life of your system.**

XPN-2RU-IP-D25L-M9

Dimensions

Height	Width	Depth
8.8 cm (3.46")	48.20 cm (18.98")	57.76 cm (22.74")

Weight

Net Weight	Gross Weight When Shipped
12.42 kg (27.38 lbs.)	19.34 kg (42.63 lbs.)

Hardware

Chassis	2RU Chassis (rackmount)
Power Supply	2x 550W single power supply Voltage Range 100-240 VAC Input Current 3.7A-7.4A
Power Consumption	@110V - Idle 170w, Under Load 450w
Fan Noise	Between 57dB to 63dB
System Drive	465G (2x 500GB 3D NAND 2.5" SSD RAID1)
Media Drive	3.8TB (2x 4TB 3D NAND 2.5" SSD in RAID1)
CPU	Intel© Xeon® Silver 4410T, 10-Core, 26.25MB Cache, 2.70GHz, 4.0 GHz Turbo
Memory	64GB (4x16GB) 4800MT/s DDR5 RDIMM with ECC
GPU	NVIDIA™ RTX 4000 Ada 20GB GDDR6, 4x Display Port 1.4a Ports
Video I/O	SMPTE ST 2110 or 2022-7 Matrox® DSXLE5L/D25/100, NDI®
O/S	Microsoft® Windows® 11 Professional for Workstation
Server Management	Integrated VGA Output 1x RJ-45 IPMI Management LAN Port

Inputs / Outputs

Video	1x Dual 25G SFP28 Cage For Up To One Channel of UHD or Four Channels of UP To 1080P (SFPs Not Included), NDI®
Audio	Embedded Audio Only SMPTE ST 2110-30
Reference	SMPTE ST 2059-2 (PTP)

NDI® is a registered trademark of VizRT NDI AB

Control

Ethernet	1x RJ-45 1G Ethernet Ports 1x RJ-45 2.5G Ethernet Ports 2x RJ-45 10G Ethernet Port
Serial	1x RS-232 Port
NMOS	IS-04 & IS-05 (JT-NM TR-1001-1)
GPI	Unlimited RossTalk™ Smart GPI over TCP/IP
USB	Front Panel - 2x USB 3.1 (Type A) Rear Panel - 4x USB 3.2 (Type A) - 2x USB 2.0 (Type A)

Included Accessories

Rackmount Kit	Slide rails, handles, and mounting hardware
Keyboard	Standard USB Windows PC Keyboard (US English)
Mouse	USB 2-button mouse
Security Key Software	Either USB Hardware License or Software-based Product Key provided with software purchased separately

Video I/O Formats

480i 29.97fps (NTSC) | 576i 25fps (PAL) | 720p 50fps | 720p 59.94fps | 720p 60fps | 1080i 25fps | 1080i 29.97fps |1080p 23.976fps | 1080p 24fps | 1080p 25fps | 1080p 29.97fps | 1080p 30fps | 1080p 50fps |1080p 59.94fps | 1080p 60fps | 1080psf 23.976fps | 1080psf 24fps | 1080psf 25fps | 1080psf 29.97fps | 1080psf 30fps | 2160p 23.976fps | 2160p 24fps | 2160p 25fps | 2160p 29.97fps | 2160p 30fps | 2160p 50fps | 2160p 59.94fps | 2160p 60fps

Supported Image File Formats

*.tga | *.tif | *.psd | *.bmp | *.jpg | *.gif | *.png

Supported Clip File Formats

AVI | MPEG† | QuickTime† | Sequential Images
† Available in the 32-bit editions only

Warranty

12-Month System Warranty (parts / labor)

ROSS