



## XPression Engines Software and Hardware Compatibility Matrix

| XPression                 | HD-SDI        |            |            |            | IP SMPTE 2022-6, 2022-7 & 2110 |                    |                      |                      | 12G SDI         |                 |                     |
|---------------------------|---------------|------------|------------|------------|--------------------------------|--------------------|----------------------|----------------------|-----------------|-----------------|---------------------|
|                           | 1RU           | 1RU        | 2RU        | 4RU        | 1RU                            | 2RU                | 4RU                  | 4RU                  | 1RU             | 2RU             | 4RU                 |
| <b>Hardware Edition ▾</b> | XPN-1RU-LL-M9 | XPN-1RU-M9 | XPN-2RU-M9 | XPN-4RU-M9 | XPN-1RU-IP-D25L-M9**           | XPN-2RU-IP-D10-M9* | XPN-2RU-IP-D25L-M9** | XPN-4RU-IP-Q25L-M9** | XPN-1RU-2G-M9†† | XPN-2RU-2G-M9†† | XPN-4RU-12G-LL-M9†† |
| <b>Software Edition ▾</b> |               |            |            |            |                                |                    |                      |                      |                 |                 |                     |
| PRIME XPRI-0001           | ●             | ●          | ●          | ●          | ●                              | ●                  | ●                    | ●                    | ●               | ●               | ●                   |
| STUDIO SCE XSTS-0001      | ●             | ●          | ●          | ●          | ●                              | ●                  | ●                    | ●                    | ●               | ●               | ●                   |
| STUDIO STANDARD XST3-0001 | ●             | ●          | ●          | ●          | ●                              | ●                  | ●                    | ●                    | ●               | ●               | ●                   |
| STUDIO FLEX XSTF-0001     | ■             | ●          | ●          | ●          | ●                              | ■                  | ●                    | ●                    | ■               | ■               | ●                   |
| BlueBox SCE XBBS-0001     | ●             | ●          | ●          | ●          | ●                              | ●                  | ●                    | ●                    | ●               | ●               | ●                   |
| BlueBox XBB3-0001         | ●             | ●          | ●          | ●          | ●                              | ●                  | ●                    | ●                    | ●               | ●               | ●                   |
| BlueBox FLEX XBBF-0001    | ■             | ●          | ●          | ●          | ●                              | ■                  | ●                    | ●                    | ■               | ■               | ●                   |
| CLIPS 1-CHANNEL XCLS-0001 | ●             | ●          | ●          | ●          | ●                              | ●                  | ●                    | ●                    | ●               | ●               | ●                   |
| CLIPS 2-CHANNEL XCLD-0001 | ■             | ●          | ●          | ●          | ●                              | ●                  | ●                    | ●                    | ●               | ●               | ●                   |
| CLIPS 4-CHANNEL XCLF-0001 | ■             | ●          | ●          | ●          | ●                              | ■                  | ●                    | ●                    | ■               | ■               | ●                   |

\*2x 10G SFP28 Cages Does Not Support UHD

\*\*2x 25G SFP28 Cages and, does not support SMPTE ST 2022-6

†† Only has 4 HD-BNCs and cannot support more than 4 signals (Supports single-channel UHD only)

†† Capabilities differ when using HD-SDI or UHD SDI inputs and/or outputs

Ross Video has a complete range of technical services available to ensure that your XPression installation is a success.

**Operational Training** can be provided at Ross Video, on-site or on the web. Experienced Ross operators will teach your staff to get the most out of your new system and enhance your production.

**Commissioning** is a service to help get your graphics system properly configured, connected, and installed. This service is performed by factory trained Ross technical staff.

**Technical Training** can be provided at Ross Video, on-site or over the web. Technical training will teach your engineering staff the technical details of the system you have purchased. System configuration, interfaces, databases, and routine maintenance procedures are some of the topics covered.

XPression comes standard with a 1-year system warranty (parts / labor & software updates) and 5-Years for Hard Disk Drives. **Extended Warranties** on hardware and software maintenance are available for an annual fee. Technical advice is available on-line, by telephone, or email to Ross Video – **Included for the life of your system.**



XPN-4RU-12G-M9

### Dimensions

| Height            | Width            | Depth              |
|-------------------|------------------|--------------------|
| 17.6 cm<br>(6.9") | 43 cm<br>(16.9") | 59.2 cm<br>(23.3") |

### Weight

| Net Weight           | Gross Weight When Shipped |
|----------------------|---------------------------|
| 25.9 kg<br>(57 lbs.) | 37.6 kg<br>(83 lbs.)      |

### Hardware

|                   |   |
|-------------------|---|
| Chassis           | 4RU Chassis (rackmount)   |
| Power Supply      | 960W EPS 12V Hot-swappable 1+1 redundant power supply                     |
| Power Consumption | @110v Idle 215w Under Full Load 450w                                      |
| Fan Noise         | Between 53dB to 58dB  |
| System Drive      | 465G (2x 500GB 3D NAND 2.5" SSD RAID1)                                    |
| Media Drive       | 7.27TB (3x 4TB 3D NAND 2.5" SSD in RAID5)                                 |
| CPU               | Intel® Xeon® Silver 4410T, 10-Core, 26.25MB Cache, 2.70GHz, 4.0 GHz Turbo |
| Memory            | 64GB (4x16GB) 4800MT/s DDR5 RDIMM with ECC                                |
| GPU               | NVIDIA™ RTX 4000 Ada 20GB GDDR6, 4x Display Port 1.4a Ports               |
| Video I/O         | HD-SDI or 12G SDI<br>Matrox® DSXLE5L/4/100, NDI®                          |
| O/S               | Microsoft® Windows® 11 Professional for Workstation                       |
| Server Management | Integrated VGA Output<br>1x RJ-45 IPMI Management LAN Port                |

### Inputs / Outputs

|           |   |
|-----------|---|
| Video     | 4x Bi-directional HD-BNC for One Channel (Video/Key Pair) Of Up To UHD and 2x Inputs Of Up To UHD |
| Audio     | Embedded Audio Only   |
| Reference | 1x Analog Black Burst (Bi-Level Sync) or Tri-Level Sync input                                     |

NDI® is a registered trademark of VizRT NDI AB

### Control

|           |  |
|-----------|--|
| Ethernet  | 1x RJ-45 1G Ethernet Ports<br>1x RJ-45 2.5G Ethernet Ports<br>2x RJ-45 10G Ethernet Port             |
| Serial    | 1x RS-232 Port   |
| Time Code | 1x LTC Input   |
| GPI       | 12 GPI In/12 GPI Out on 25-pin D-Sub Connector, Unlimited RossTalk™ Smart GPI over TCP/IP            |
| USB       | Front Panel<br>- 2x USB 3.1 (Type A)<br>Rear Panel<br>- 4x USB 3.2 (Type A)<br>- 2x USB 2.0 (Type A) |

### Included Accessories

|                       |   |
|-----------------------|---|
| Rackmount Kit         | Slide rails, Handles, and Mounting Hardware   |
| Keyboard              | Standard USB Windows PC Keyboard (US English)   |
| Mouse                 | USB 2-button mouse  |
| Security Key Software | Either USB Hardware License or Software-based Product Key Provided With Software Purchased Separately |

### Video I/O Formats

480i 29.97fps (NTSC) | 576i 25fps (PAL) | 720p 50fps | 720p 59.94fps | 720p 60fps | 1080i 25fps | 1080i 29.97fps | 1080p 23.976fps | 1080p 24fps | 1080p 25fps | 1080p 29.97fps | 1080p 30fps | 1080p 50fps | 1080p 59.94fps | 1080p 60fps | 1080p 23.976fps | 1080psf 24fps | 1080psf 25fps | 1080psf 29.97fps | 1080psf 30fps | 2160p 23.976fps | 2160p 24fps | 2160p 25fps | 2160p 29.97fps | 2160p 30fps | 2160p 50fps | 2160p 59.94fps | 2160p 60fps

### Supported Image File Formats

\*.tga | \*.tif | \*.psd | \*.bmp | \*.jpg | \*.gif | \*.png

### Supported Clip File Formats

AVI | MPEG1 | QuickTime† | Sequential Images

†Available in the 32-bit editions only

### Warranty

12-Month System Warranty (parts / labor)

Specifications subject to change without notice

Phone: +1 613-652-4886 • Technical Support: 1-844-652-0645 (North America), +800 1005 0100 (International) • 3509DR-568-01 • April 2024

©2024 Ross Video Limited. Ross®, and any related marks are trademarks or registered trademarks of Ross Video Limited. All other trademarks are the property of their respective companies. PATENTS ISSUED and PENDING. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, mechanical, photocopying, recording or otherwise, without the prior written permission of Ross Video. While every precaution has been taken in the preparation of this document, Ross Video assumes no responsibility for errors or omissions. Neither is any liability assumed for damages resulting from the use of the information contained herein.