

XPression Project Server, INcoder and Data Server User Supplied Hardware Platform

This document describes the Ross recommended hardware configuration for XPression Project Server, INcoder, and Data Server (Chameleon) systems in which a customer or business partner supplies hardware. Bundled hardware and software solutions are also available from Ross Video.

Supported hardware is updated regularly with the latest information on processors, I/O boards, Hard Disk Drives, and more. Please read the specifications below to select the appropriate hardware to best meet the specific needs of your application.

Ross provides these recommendations on a best-efforts basis and cannot guarantee specific hardware performance parameters. Hardware performance and functionality is the responsibility of the hardware vendor. Customers or business partners supplying hardware are responsible for hardware installation, configuration, setup, and support.

Please feel free to contact us with questions at solutions@rossvideo.com.

Specifications subject to change.

Third-Party Copyright and Trademarks

All third-party product names and any registered and unregistered trademarks mentioned in this document are used for identification purposes only and remain the exclusive property of their respective owners.

Specifications

Component	Minimum	Recommended	Tested Components
Power Supply	Select a power supply based on the power and connection requirements of the system components. It is recommended to operate most computer power supplies at 40% to 80% of their total capacity for optimal efficiency and overhead.		960 W EPS 12 V hot-swappable 1+1 redundant power supply
Memory	16 GB	64 GB	64 GB (4 x 16 GB) 4800 MT/s MHz DDR5 RDIMM with ECC
GPU	GPU for connection to video monitor	NVIDIA® T400, 2 GB GDDR6, 3 x Mini Display Port 1.4a Ports	NVIDIA® RTX A400, 4 GB GDDR6, 4 x Mini Display Port 1.4a
Mainboard	Select a mainboard that can support the requirements of your system components.		ATX Server Motherboard
CPU	6 CPU Cores @ 2.8 GHz (XPression is optimized for Intel® CPUs)	8 CPU Cores @ 3.6 GHz (XPression is optimized for Intel® CPUs)	Intel® Xeon® Silver 2455, 12-Core, 30 MB Cache, 3.2 GHz, 4.6 GHz Turbo Frequency
Network	1x RJ-45 1 G Ethernet Port	1x RJ-45 1 G Ethernet Port 1x RJ-45 10 G Ethernet Port	1x RJ-45 1 G Ethernet Port 1x RJ-45 2.5 G Ethernet Port 1x RJ-45 10 G Ethernet Port

Component	Minimum	Recommended	Tested Components
Storage	100 GB	• System Storage: 256 GB SSD • System RAID: RAID 1 (Mirrored) • Media Storage: 1 TB SSD or HDD • Media RAID: RAID 1 or RAID 5	• System Storage: 2 x 512 GB SSD RAID 1 (Mirrored) • Media Storage: 2 x 4 TB SSD RAID 1
USB	• 1 USB port for XPression USB License • 1 USB port for XPression Software Installer USB • 2 USB ports for keyboard and mouse	• 1 USB port for XPression USB License • 1 USB port for XPression Software Installer USB • 2 USB ports for keyboard and mouse	• 1 USB port for XPression USB License • 1 USB port for XPression Software Installer USB • 2 USB ports for keyboard and mouse
Keyboard / Mouse	• Standard keyboard / 2 button mouse • Optional: XPression Custom Keyboard	• Standard keyboard / 2 button mouse • Optional: XPression Custom Keyboard	• Standard keyboard / 2 button mouse • Optional: XPression Custom Keyboard
Operating System	Microsoft® Windows® 10 Professional, 64-bit	Microsoft® Windows® 11 Professional for Workstation 64-bit	Microsoft® Windows® 11 Professional for Workstation 64-bit