# **XPression**

## **2RU IP Dual 10G Chassis**



### XPression Engines Software and Hardware Compatibility Matrix

XPression	HD-SDI			IP SMPTE ST 2022-6, 2022-7 & 2110				12G SDI					
	1RU	1RU	2RU	4RU	1RU	2F	RU	4RU	4RU	1RU	2RU	4F	RU
Hardware Edition ▶  Software Edition ▼	XPN-1RU-LL-M9				XPN-1RU-IP-D25L-M9**					XPN-1RU-12G-M9 <sup>††</sup>			XPN-4RU-12G-LL-M9 <sup>##</sup>
PRIME XPR1-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
STUDIO SCE XSTS-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
STUDIO STANDARD XST3-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
STUDIO FLEX XSTF-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
BlueBox SCE XBBS-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
BlueBox XBB3-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
BlueBox FLEX XBBF-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
CLIPS 1-CHANNEL XCLS-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
CLIPS 2-CHANNEL XCLD-0001	•	•	•	•	•	•	•	•	•	•	•	•	•
CLIPS 4-CHANNEL XCLF-0001	•	•	•	•	•	•	•	•	•	•	•	•	•

Ross Video has a complete range of technical services available to ensure that your XPression installation is a success.

Operational Training can be provided at Ross Video, on-site or on the web. Experienced Ross operators will teach your staff to get the most out of your new system and enhance your production.

Commissioning is a service to help get your graphics system properly configured, connected, and installed. This service is performed by factory trained Ross technical staff.

**Technical Training** can be provided at Ross Video, on-site or over the web. Technical training will teach your engineering staff the technical details of the system you have purchased. System configuration, interfaces, databases, and routine maintenance procedures are some of the topics covered.

XPression comes standard with a 1-year system warranty (parts / labor & software updates) and 5-Years for Hard Disk Drives. Extended Warranties on hardware and software maintenance are available for an annual fee. Technical advice is available on-line, by telephone, or email to Ross Video Included for the life of your system.



<sup>\*2</sup>x 10G SFP28 Cages Does Not Support UHD
\*\*2x 25G SFP28 Cages and, does not support SMPTE ST 2022-6
\*\*Only has 4 HD-BNCs and cannot support more than 4 signals (Supports single-channel UHD only)
\*\*Capabilities differ when using HD-SbI or UHD SDI inputs and/or outputs

# **XPression**

## 2RU IP Dual 10G Chassis



XPN-2RU-IP-D10-M9

#### **Dimensions**

	Height	Width	Depth
42.	.8 mm	48.20 cm	57.76 cm
(1.6	8")	(18.98")	(22.74")

#### Weight

Net Weight	Gross Weight When Shipped
	19.34 kg (42.63 lbs.)

#### Hardware

naraware	
Chassis	2RU Chassis (rackmount)
Power Supply	2x 550W single power supply Voltage Range 100-240 VAC Input Current 3.7A-7.4A
Power Consumption	@110V - Idle 170w, Under Load 450w
Fan Noise	Between 57dB to 63dB
System Drive	465G (2x 500GB 3D NAND 2.5" SSD RAID1)
Media Drive	3.8TB (2x 4TB 3D NAND 2.5" SSD in RAID1)
CPU	Intel <sup>©</sup> Xeon Silver 4410T, 10-Core, 26.25MB Cache, 2.70GHz, 4.0 GHz Turbo
Memory	64GB (4x16GB) 4800MT/s DDR5 RDIMM with ECC
GPU	NVIDIA™ RTX 4000 Ada 20GB GDDR6, 4x Display Port 1.4a Ports
Video I/O	SMPTE ST 2022-6 or 2110 and 2022-7 Matrox® DSXLE4L/E4/100, NDI®
O/S	Microsoft® Windows® 11 Professional for Workstation
Server Management	Integrated VGA Output 1x RJ-45 IPMI Management LAN Port

#### Inputs / Outputs

Video	1x Dual 10G SFP28 Cage (SFPs Not Included)
Audio	Embedded Audio Only
Reference	1x Analog Black Burst (Bi-Level Sync) or Tri-Level Sync input, SMPTE ST 2059-2 (PTP) for 2022-6, SMPTE ST 2059-2 (PTP) for 2110

NDI® is a registered trademark of VizRT NDI AB

#### Control

Control	
	1x RJ-45 1G Ethernet Ports
Ethernet	1x RJ-45 2.5G Ethernet Ports
	2x RJ-45 10G Ethernet Port
Serial	1x RS-232 Port
NMOS	IS-04 & IS-05 (JT-NM TR-1001-1)
GPI	Unlimited RossTalk™ Smart GPI over TCP/IP
	Front Panel
	- 2x USB 3.1 (Type A)
USB	Rear Panel
	- 4x USB 3.2 (Type A)
	- 2x USB 2.0 (Type A)

#### Included Accessories

included / tecessories				
Rackmount	Slide rails, handles, and mounting			
Kit	hardware			
Keyboard	Standard USB Windows PC			
	Keyboard (US English)			
Mouse	USB 2-button mouse			
Security Key Software	Either USB Hardware License or			
	Software-based Product Key			
	provided with software purchased			
	separately			

#### Video I/O Formats

480i 29.97 fps (NTSC) | 576i 25 fps (PAL) | 720p 50 fps | 720p 59.94 fps | 720p 60 fps | 1080i 25 fps | 1080i 29.97 fps | 1080p 23.976 fps | 1080p 29.97 fps | 1080p 50 fps | 1080p 59.94 fps | 1080p 60 fps | 1080psf 23.976 fps | 1080psf 24 fps| 1080psf 25 fps | 1080psf 29.97 fps | 1080psf 30 fps

#### Supported Image File Formats

\*.tga | \*.tif | \*.psd | \*.bmp | \*.jpg | \*.gif | \*.png

#### Supported Clip File Formats

AVI | MPEG† | QuickTime† | Sequential Images

#### Warranty

12-Month System Warranty (parts / labor)

