XPression

4RU IP Quad 25G Chassis



XPression Engines Software and Hardware Compatibility Matrix

| XPression | HD-SDI | | | IP SMPTEST 2022-6, 2022-7 & 2110 | | | | 12G SDI | | | | | |
|--|---------------|-----|-----|-------------------------------------|----------------------|----|----|---------|----------------------|------------------------------|------------------------------|------------------------------|----------------------------------|
| | 1RU | 1RU | 2RU | 4RU | 1RU | 2F | ₹U | 4RU | 4RU | 1RU | 2RU | 4F | N. |
| Hardware Edition ▶ Software Edition ▼ | XPN-1RU-LL-M9 | | | XPN-4RU-M9 | XPN-1RU-IP-D25L-M9** | | | | XPN-4RU-IP-Q25L-M9** | XPN-1RU-12G-M9 ^{††} | XPN-2RU-12G-M9 ^{††} | XPN-4RU-12G-M9 ^{††} | XPN-4RU-12G-LL-M9 ^{†††} |
| PRIME XPR1-0001 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| STUDIO SCE XSTS-0001 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| STUDIO STANDARD XST3-0001 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| STUDIO FLEX XSTF-0001 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| BlueBox SCE XBBS-0001 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| BlueBox XBB3-0001 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| BlueBox FLEX XBBF-0001 | • | • | • | • | • | • | • | • | • | • | • | - | • |
| CLIPS 1-CHANNEL XCLS-0001 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| CLIPS 2-CHANNEL XCLD-0001 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| CLIPS 4-CHANNEL XCLF-0001 | | • | • | • | • | • | • | • | • | • | • | • | • |

^{*2}x 10G SFP28 Cages Does Not Support UHD
*2x 26G SFP28 Cages and, does not support SMPTE ST 2022-6
"I Only has 4 HD-BNCs and cannot support more than 4 signals (supports single-channel UHD only)
"I'Capabilities differ when using HD-SDI or UHD SDI inputs and/or outputs

Ross Video has a complete range of technical services available to ensure that your XPression installation is a success.

Operational Training can be provided at Ross Video, on-site or on the web. Experienced Ross operators will teach your staff to get the most out of your new system and enhance your production.

Commissioning is a service to help get your graphics system properly configured, connected, and installed. This service is performed by factory trained Ross technical staff.

Technical Training can be provided at Ross Video, on-site or over the web. Technical training will teach your engineering staff the technical details of the system you have purchased. System configuration, interfaces, databases, and routine maintenance procedures are some of the topics covered.

XPression comes standard with a 1-year system warranty (parts / labor & software updates) and 5-Years for Hard Disk Drives. **Extended Warranties** on hardware and software maintenance are available for an annual fee. Technical advice is available on-line, by telephone, or email to Ross Video – **Included for the life of your system**.

XPression

4RU IP Quad 25G Chassis



XPN-4RU-IP-Q25-M9

Dimensions

| | Height | Width | Depth |
|---|---------|---------|---------|
| ſ | 17.6 cm | 43 cm | 59.2 cm |
| | (6.9") | (16.9") | (23.3") |

Weight

| Net Weight | Gross Weight When Shipped |
|------------|---------------------------|
| 25.9 kg | 37.6 kg |
| (57 lbs.) | (83 lbs.) |

Hardware

| riaraware | |
|----------------------|--|
| Chassis | 4RU Chassis (rackmount) |
| Power Supply | 960W EPS 12V Hot-swappable 1+1 Redundant Power Supply |
| Power Consumption | @110v Idle 215w Under Full Load 450w |
| Fan Noise | Between 53dB to 58dB |
| System Drive | 465G (2x 500GB 3D NAND 2.5" SSD RAID1) |
| Media Drive | 7.27TB (3x 4TB 3D NAND 2.5" SSD in RAID5) |
| CPU | Intel [©] Xeon Silver 4410T, 10-Core, 26.25MB Cache, 2.70GHz, 4.0 GHz Turbo |
| Memory | 64GB (4x16GB) 4800MT/s DDR5 RDIMM with ECC |
| GPU | NVIDIA™ RTX 4000 Ada 20GB GDDR6, 4x Display Port 1.4a Ports |
| Video I/O | SMPTE ST 2022-7 or SMPTE ST 2110 Matrox [®] X.mio5/Q25/100, NDI [®] |
| O/S | Microsoft® Windows® 11 Professional for Workstation |
| Server Management | Integrated VGA Output 1x RJ-45 IPMI Management LAN Port |

Inputs / Outputs

| Video | 2x Dual 25G SFP28 Cages For Up To One Channel of UHD or Four Channels of Up To 1080P (SFPs Not Included) |
|-----------|--|
| Audio | Embedded Audio Only SMPTE ST 2110-30 |
| Reference | SMPTE ST 2059-2 (PTP) |

NDI® is a registered trademark of VizRT NDI AB

Control

| Ethernet | 1x RJ-45 1G Ethernet Ports 1x RJ-45 2.5G Ethernet Ports 2x RJ-45 10G Ethernet Port |
|-----------|---|
| Serial | 1x RS-232 Port |
| NMOS | IS-04 & IS-05 (JT-NM TR-1001-1) |
| Time Code | 1x LTC Input |
| GPI | 12 GPI In/12 GPI Out on 25-pin D-Sub Connector, Unlimited RossTalk™ Smart GPI over TCP/IP |
| USB | Front Panel - 2x USB 3.1 (Type A) Rear Panel - 4x USB 3.2 (Type A) - 2x USB 2.0 (Type A) |

Included Accessories

| Rackmount Kit | Slide rails, Handles, and Mounting Hardware | | | |
|--------------------------|---|--|--|--|
| Keyboard | Standard USB Windows PC Keyboard (US English) | | | |
| Mouse | USB 2-button mouse | | | |
| Security Key Software | Either USB Hardware License or Software-based Product Key Provided With Software Purchased Separately | | | |

Video I/O Formats

480i 29.97fps (NTSC) | 576i 25fps (PAL) | 720p 50fps | 720p 59.94fps | 720p 60fps | 1080i 25fps | 1080i 29.97fps | 1080p 23.976fps | 1080p 24fps | 1080p 25fps | 1080p 29.97fps | 1080p 30fps | 1080p 50fps | 1080p 59.94fps | 1080p 60fps | 1080psf 23.976fps | 1080psf 24fps | 1080psf 25fps | 1080psf 29.97fps | 1080psf 2160p 23.976fps | 2160p 23.976fps | 2160p 24fps | 2160p 24fps | 2160p 25fps | 2160p 29.97fps | 2160p 29.97fps | 2160p 50fps | 2160p 50

Supported Image File Formats

*.tga | *.tif | *.psd | *.bmp | *.jpg | *.gif | *.png

Supported Clip File Formats

AVI | MPEG† | QuickTime† | Sequential Images
†Available in the 32-bit editions only

Warranty

12-Month System Warranty (parts / labor)

Specifications subject to change without notice

