**XPression** 

# XPression Tick-it Core Server Hardware Specifications



#### **Dimensions**

| Height          | Width             | Depth             |
|-----------------|-------------------|-------------------|
| 4.28 cm (1.68") | 48.20 cm (18.98") | 57.76 cm (22.74") |

#### Weight

| Net Weight            | Gross Weight When<br>Shipped |
|-----------------------|------------------------------|
| 12.42 kg (27.38 lbs.) | 19.34 kg (42.63 lbs.)        |

#### **Hardware**

| Chassis             | 1 RU chassis (rack-mount)                                                                  |
|---------------------|--------------------------------------------------------------------------------------------|
| Power Supply        | 550W redundant supplies<br>Voltage Range 100-240 VAC<br>Input Current 7.4 A- 3.7 A         |
| System Drives       | 2x 256GB SSD RAID 1 (Mirrored)                                                             |
| Media Drives        | 2x 1TB SSD RAID 1 (Mirrored)                                                               |
| CPU                 | Intel© Core i7-8700K, 6 Core, 12MB Cache, 3.7GHz, 4.7Ghz Turbo                             |
| Memory              | 16GB (2x8GB) 2666MHz DDR4 UDIMM<br>Non-ECC                                                 |
| GPU                 | NVIDIA® Quadro P400, 2GB GDDR5,<br>256 CUDA® Cores, 3x Mini Display Port<br>1.4 Connectors |
| Operating<br>System | Microsoft® Windows® 10 Professional 64-bit                                                 |

#### **Control**

| Ethernet | 1x RJ-45 1G Ethernet Port<br>1x RJ-45 10G Ethernet Port                                                                  |
|----------|--------------------------------------------------------------------------------------------------------------------------|
| GPI      | RS-232 Serial GPI, RossTalk/Smart GPI through TCP/IP                                                                     |
| USB      | Front Panel: 2x USB 3.1 (Type A) 1x USB 3.1 (Type C)/iGFX Display Port Rear Panel: 2x USB 3.1 (Type C)/iGFX Display Port |

#### **Temperature and Humidity**

| Temperature          | Operating: 10°C to 35°C (50°F to 95°F)                                                                                                            |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                | Storage: -40°C to 65°C (-40°F to 149°F)                                                                                                           |
| Relative<br>Humidity | Operating: 10% to 85% (Max dew point temperature = 40°C) (non-condensing) Storage: 10% to 90% (Max dew point temperature = 60°C) (non-condensing) |

#### **Included Accessories**

| Rackmount Kit | Slide rails, handles, and mounting hardware |
|---------------|---------------------------------------------|
| USB           | 2x USB Type C to USB Type A Adapters        |
| Keyboard      | Standard USB PC Keyboard                    |
| Mouse         | USB mouse                                   |



# **XPression**

## **Included Software**

- Microsoft® Windows® 10 Professional 64-bit O/S
- XPression software package

## Warranty

12 Month System Warranty (parts / labor and software updates)

Specifications subject to change.

